



**DECONTAMINATION OF CADMIUM CONTAINING
AQUEOUS SOLUTIONS USING FELDSPAR**

A PROJECT REPORT PRESENTED BY

UDARA RASIKA DHARMASIRI

to the Board of Study in Chemical Sciences of the
POST GRADUATE INSTITUTE OF SCIENCE

*in partial fulfillment of the requirement
for the award of the degree of*

MASTER OF SCIENCE IN ANALYTICAL CHEMISTRY

of the

**UNIVERSITY OF PERADENIYA
SRI LANKA
2006**

607443

DECONTAMINATION OF CADMIUM CONTAINING AQUEOUS SOLUTIONS BY USING FELDSPAR

Udara Rasika Dharmasiri

Postgraduate Institute of Science
Peradeniya, Sri Lanka

Contamination of water by toxic heavy metal is becoming a serious environmental issue in the present day world. Cadmium, in particular, is a major water pollutant in industrial effluent, and considered to be very harmful due to the highly toxic nature and its tendency to accumulate in the tissues of living organisms. Feldspar, among many natural substances such as saw-dust, kaolinite, marine macro algal, grape stalk and chitin, can be utilized to remove cadmium from effluent waters.

The studies were basically carried out to characterize feldspar, to optimize the experimental parameters such as equilibrium time, shaking time particle size, pH, adsorbate concentration and temperature, and to evaluate the isotherms, kinetics and isosteric heat of adsorption.

Characterization of feldspar revealed that majority of feldspar used in this study is consisted of orthoclase. The surface charge of feldspar was determined by potentiometric methods and the point of zero charge of the feldspar is in between pH 6.0 - 6.5. Surface specific area was determined by methylene blue adsorption method and specific surface area is $14.68 \text{ m}^2 \text{ g}^{-1}$. Prior to determine the surface area of feldspar, surface areas of standard samples of gibbsite and kaolinite were determined to calibrate the system. According to the isosteric heat of adsorption, feldspar surface is homogeneous under physicochemical conditions applied in this study.

The percent removal cadmium initially increases rapidly with the increasing equilibration time reaching a plateau after of 3 hours where no significant effect on shaking time is observed. As expected, the percent removal is largely affected by the diameter of feldspar particles due to the fact that increasing the effective surface area enhances the surface energy by increasing the number of adsorption sites. Experiments done by changing solution pH suggest that cadmium removal increase at highly basic conditions. Presence of phosphate, sulphate and chloride reduce the removal efficiency of cadmium.

The adsorption of cadmium ions on feldspar follows both Langmuir ($R^2 = 0.9859$) and Freundlich ($R^2 = 0.9926$) adsorption isotherms suggesting an initial monolayer coverage of cadmium ions on feldspar particles, followed by multilayer coverage. Reaction rate studies indicate that the removal of cadmium by feldspar follows first order kinetics including initial fast adsorption and subsequent slower adsorption.

These results can be utilized to design an efficient, low cost and environmental friendly methodology for removal of cadmium from effluents.

Key words: Feldspar /Cadmium /adsorption /kinetics /surface charge /surface area /isosteric heat