AUTHOR AMARATUNGA, DI

ORIGINAL TITLE An Experimental study of posterior composite restorations during

occlusal stresses

DEGREE M.Phil. YEAR 1998

INSTITUTE University of Peradeniya

LOCATION UP(MED)

MAIN HEADING DENTAL RESTORATION, PERMANENT

ABSTRACT

An in vitro study of posterior composite restorations was carried out in order to study the behavior of composite restorations in posterior teeth and to find out the best cavity preparation desii,'11 for posterior composite restorations. One hundred and thirty five human upper premolar teeth extracted for orthodontic purposes were used to prepare 4 different types of cavities. The first cavity type was prepared using the Black's method. The second type preparation comprised of a interproximal box preparation similar to that of Black's technique with the exception of the occlusal dovetail being prepared within enamel. Third type of cavity, was prepared according to the Elderton's method, while, the new suggested cavity preparation which is the fourth was designed to a cylindrical shape without an occlusal preparation. Tooth samples from each cavity type were filled using TPH (a hybrid composite material) and Tetric (a microhybrid composite restorative material). In addition, amalgam was used only for cavities prepared using Black's method for the purpose of comparison. All the restorations were subjected to occl usal force of 70 Newton at a frequency of70-120 cycles per minute. Samples were examined for changes and failures after each 25,000 cycles up to maximum of 250,000 cycles. Four types of failures, namely, Loss of Material, Surface Failure, Crevice Formation and Crack Initiation were studied. Scanning electron microscopic pictures were taken from certain selected samples for the confirmation of the above failures detected using the magnifying glass and explorer As the data were characterized by binary (binomial) distribution, the linear logistic model was fitted for these data to estimate the Proportion of failure (p) at different number of stress cycles. Data collected from the study shows better overall performances of the restorations carried out using the suggested cylindrical cavity preparation and the Elderton's method i.e. cavities prepared without an occlusal dovetail, than the cavities with an occlusal dovetail, when composite is used as a restorative material. Amalgam restorations however, performed well in Black's cavities prepared with an occlusal dovetail. Although the Loss of Material and Surface Failure were commonly seen in composite restorations, Crevice Fonnation and Crack Initiation were more in amalgam restorations. There was no sil, '1lificant difference of the performances between Tetric and TPH composite materials. As such the newly suggested Cylindrical cavity design could be recommended for class II composite

restorations. Black's cavity preparation design should not be used when composite restorations are carried out for class II cavities.